



ARTEL

www.rrpelletkachel.nl

**NIEUW IN HET
ASSORTIMENT**


















Pelletketel Compact



auto clean



Artel Compact		16 kW		20 kW		24 kW		28 kW		34 kW	
	Eenheid	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min.
 POWER Vermogen	kW	16.2	4.9	19	5,86	23,8	5,86	27,17	7	31,8	7
 POWER Verm. water	kW	14.4	4.29	17,5	5,21	21,5	5,21	24,5	6,34	29,14	6,34
 Rendement	%	89.1	87,8	92,1	88,8	90,4	88,8	90,1	90,5	91,6	90,6
 Rookgas Temp.	°C	130	63	135	63	140	63	145	89	150	89
 Min. afv. druk	Pa	12	12	12	12	12	12	12	12	12	12
 Afvoer Diam.	mm	Ø 80		Ø 80		Ø 80		Ø 100		Ø 100	
 Inlaat Diam.	mm	Ø 50		Ø 50		Ø 50		Ø 60		Ø 60	
 CV aansluiting	Inch	3/4		3/4		3/4		3/4		3/4	
 Ketel Liter inh.	l	20		50		50		60		60	
 Pellettank Inh.	kg	46		65		65		85		85	
 Pellet diameter	mm	Ø 6		Ø 6		Ø 6		Ø 6		Ø 6	
 Verbruik / uur	kg/h	3,3	1,02	3,8	1,2	4,8	1,2	5,5	1,4	6,5	1,4
 Branduren/tank	h	45	13.5	50	12.5	50	12.5	56.5	11.5	56.5	11.5
 Oppervlakte	m ³	* 300		* 380		* 430		* 540		*620	
 Gewicht	kg	180		250		250		305		305	
Afmeting	HxBxD	1081x562 x701		1240x610 x786		1240x610 x786		1358x670 x866		1358x670 x866	
Gloei Bougie		Keramisch		Keramisch		Keramisch		Keramisch		Keramisch	
Subsidie	RVO	Ja		Ja		Ja		Ja		Ja	

* Verwambaar volume is gebaseerd op een redelijk tot goed geïsoleerde woning met een kamer hoogte van 260cm.